

**ARMADI REFRIGERATI GN 2/1 e 600x400**

**EKO**

REFRIGERATED CABINETS GN 2/1 and 600x400  
ARMOIRES RÉFRIGÉRÉES GN 2/1 et 600x400  
GN 2/1 und 600x400 KÜHL- und TIEFKÜHLSCHRÄNKE

**EKO**  
**GN 2/1**  
**STANDARD**

**EKO**  
**600x400**  
**STANDARD**



**TECNODOM**  
Energy Saving and  
Eco Technology

2011

**N°4**

**TECNODOM**<sup>®</sup>  
spa  
refrigerazione

## Cod. AFI 4EKOMBT

400

**Armadio Refrigerato GN 2/1 monoblocco in Acciaio Inox a bassa temperatura con 2 porte**

2 doors Low Temperature Stainless Steel GN 2/1 Refrigerated Cabinet - Armoire Réfrigérée GN 2/1 en Acier Inox basse température avec 2 portes -  
Edelstahl-Tiefkühlschrank GN 2/1 mit Monoblockaggregat und mit 2 Türen

**-18/-22°C**

DIMENSIONI - DIMENSIONS DIMENSIONS - MABE	WxDxH mm	<b>1420x800x2030/2100</b>
DIMENSIONI IMBALLO - PACKAGING DIMENSIONS DIMENSIONS D'EMBALLAGE - MABE VERPACKUNG	WxDxH mm	<b>1460x840x2200</b>
PESO NETTO - NET WEIGHT POIDS NET - NETTOGEWICHT	kg	<b>159</b>
CAPACITA' NETTA - NET CAPACITY CAPACITÉ NET - NUTZINHALT	l	<b>1400</b>
TEMPERATURA D'ESERCIZIO - WORKING TEMPERATURE TEMPÉRATURE DE SERVICE - ARBEITSTEMPERATUR	°C	<b>-18 / -22</b>
GAS REFRIGERANTE - GAS GAZ RÉFRIGÉRANT - KÄLTEMITTEL	GAS	<b>R404A/R507</b>
COLLAUDO - TEST DETAILS DETAILS D'ESSAI - PRÜFUNGSERGEBNISSE	°C / RH	<b>+43 / 65%</b>
ASSORBIMENTO ELETTRICO - ABSORBED POWER PUISSANCE ABSORBÉE - ANSCHLUBWERT	W	<b>700</b>
ALIMENTAZIONE - POWER SUPPLY ALIMENTATION - NETZSPANNUNG	V-P-Hz	<b>230-1-50</b>

**Dotazione per allestimento interno:** 6 Griglie plastificate Rilsan GN 2/1 e 12 guide in Acciaio Inox, Fermo ventole - **Internal standard set-up:** 6 plastic-coated Rilsan grids GN 2/1 and 12 Stainless Steel Runners, Door micro switches - **Composition Standard:** 6 Clayettes plastifiées Rilsan et 12 glissières en Acier Inox, Arrêt ventilation - **Standardausstattung:** 6 rilsanierte Roste GN 2/1 und 6 paar Edelstahlschienen, Lüftungstop



## Cod. A4I 4EKOMBT

400

**Armadio Refrigerato GN 2/1 monoblocco in Acciaio Inox a bassa temperatura con 4 sportelli**

4 half doors Low Temperature Stainless Steel GN 2/1 Refrigerated Cabinet - Armoire Réfrigérée GN 2/1 en Acier Inox basse température avec 4 portes -  
Edelstahl-Tiefkühlschrank GN 2/1 mit Monoblockaggregat, mit 4 Halbtüren

**-18/-22°C**

DIMENSIONI - DIMENSIONS DIMENSIONS - MABE	WxDxH mm	<b>1420x800x2030/2100</b>
DIMENSIONI IMBALLO - PACKAGING DIMENSIONS DIMENSIONS D'EMBALLAGE - MABE VERPACKUNG	WxDxH mm	<b>1460x840x2200</b>
PESO NETTO - NET WEIGHT POIDS NET - NETTOGEWICHT	kg	<b>165</b>
CAPACITA' NETTA - NET CAPACITY CAPACITÉ NET - NUTZINHALT	l	<b>1400</b>
TEMPERATURA D'ESERCIZIO - WORKING TEMPERATURE TEMPÉRATURE DE SERVICE - ARBEITSTEMPERATUR	°C	<b>-18 / -22</b>
GAS REFRIGERANTE - GAS GAZ RÉFRIGÉRANT - KÄLTEMITTEL	GAS	<b>R404A/R507</b>
COLLAUDO - TEST DETAILS DETAILS D'ESSAI - PRÜFUNGSERGEBNISSE	°C / RH	<b>+43 / 65%</b>
ASSORBIMENTO ELETTRICO - ABSORBED POWER PUISSANCE ABSORBÉE - ANSCHLUBWERT	W	<b>700</b>
ALIMENTAZIONE - POWER SUPPLY ALIMENTATION - NETZSPANNUNG	V-P-Hz	<b>230-1-50</b>

**Dotazione per allestimento interno:** 8 Griglie plastificate Rilsan GN 2/1 e 16 guide in Acciaio Inox, Fermo ventole - **Internal standard set-up:** 8 plastic-coated Rilsan grids GN 2/1 and 16 Stainless Steel Runners, Door micro switches - **Composition Standard:** 8 Clayettes plastifiées Rilsan et 16 glissières en Acier Inox, Arrêt ventilation - **Standardausstattung:** 8 rilsanierte Roste GN 2/1 und 8 paar Edelstahlschienen, Lüftungstop

